

# PROVA 3007S

## Flexible Current Probes (3000A)



### Electrical Specifications:

Please refer to PROVA 6830A+3007S.

## Features:

- Flexible current probes (3pcs. per set) for PROVA 6830A power analyzer only.
- Range selection: Manual (300A, 3000A).
- 3P4W, 3P3W, 1P2W, 1P3W.



## General Specifications: (3pcs. per set)

Probe Length 3007-24	24 in / 637mm
Minimum Bending Diameter:	16mm
Connector Diameter:	12.3mm
Cable Diameter:	8.5mm
Cable Length from Probe to Box:	1700mm
Cable Length from Box to Output:	1700mm
Range selection:	Manual (300A, 3000A)
Dimension (Box):	63.2mm (L) x 40.3mm (W)x 28.5mm (H) 2.5" (L) x 1.6" (W) x 1.1" (H)
Battery:	Powered by power analyzer
Operating Temperature:	0°C to 50°C
Operating Humidity:	15% to 85% RH
Altitude:	up to 2000M
Storage Temperature:	-20°C to 60°C
Storage Humidity:	15% to 75% RH
Weight:	320g per pc., 3pcs. per set
Accessory:	Users manual x 1

# PROVA

## PROVA INSTRUMENTS INC.

Add: 6F-2, No. 129, Lane 235, Pao-Chiao Road,  
Shin-Tien District, New Taipei City 23145,  
Taiwan

Tel: 886-2-89191255

Fax: 886-2-89191489

E-mail: [prova@ms3.hinet.net](mailto:prova@ms3.hinet.net)

[www.prova.com.tw](http://www.prova.com.tw)