

# PROVA AA5

## AC/DC Current Probe

CE  
IEC 61010

CAT III  
600V

CAT II  
1000V



### Features:

1. Accurate AC/DC current probe for measuring **0~200A**
2. High Resolution: **AC 1mA, DC 10mA**
3. **25mm** Large Jaw Diameter
4. One Touch Zero for DCA adjustment
5. Connect to DMM or Oscilloscope
6. Easy single rotary switch for any function selection

## Electrical Specifications: (23°C±5°C, CF≤3)

Range	Output	Accuracy of Reading
DCA 0-40A	DC 10mV/A	±1.0%±0.02A
DCA 0-150A	DC 1mV/A	±1.0%±0.2A
DCA 150-200A		-2.2%±0.2A
ACA 0-4A	AC 100mV/A	±2.0%±0.005A (40-400Hz)
ACA 0-40A	AC 10mV/A	±1.5%±0.03A (40-1KHz)
ACA 0-150A	AC 1mV/A	±1.5%±0.3A (40-1KHz)
ACA 150-200A		-2.5%±0.3A (40-400Hz)

Range	Sensitivity
DCA 0-40A	0.1mV/10mA DC
DCA 0-200A	0.1mV/100mA DC
ACA 0-4A	0.1mV/1mA AC
ACA 0-40A	0.1mV/10mA AC
ACA 0-200A	0.1mV/100mA AC

## General Specifications: (Indoor Use)

Conductor Size:	25mm max. (approx.)
Battery Type:	two 1.5V LR03 AAA
Range Selection:	Manual
Power Consumption:	22mA (approx.)
Low battery Indication:	red LED lights
Operating Temperature:	-10°C to 50°C
Operating Humidity:	less than 85% relative
Altitude:	up to 2000M
Storage Temperature:	-20°C to 60°C
Storage Humidity:	less than 75% relative
Dimension:	152mm (L) x 66mm (W) x 36mm (H) 6.0" (L) x 2.6" (W) x 1.4" (H)
Weight:	250g (battery included)
Accessories:	Carrying bag, Users manual, 1.5V Battery x 2

# PROVA

## PROVA INSTRUMENTS INC.

**Add:** 6F-2, No. 129, Lane 235, Pao-Chiao Road,  
Shin-Tien District, New Taipei City 23145,  
Taiwan

**Tel:** 886-2-89191255

**Fax:** 886-2-89191489

**E-mail:** [prova@ms3.hinet.net](mailto:prova@ms3.hinet.net)

**www.prova.com.tw**